

Brisa

Minimalist design

Roca



Practical and adaptable

A shower enclosure with a slim profile and a wide range of versions and profiles in a polished silver or matt black finish.

2000 mm height

Brisa, with a height of two meters, prevents splashing outside the shower area.

8 mm glass thickness

Maximum safety tempered glass (following the European standard EN:12150) that shatters into even tiny pieces, ensuring maximum safety during use.

Compact profiles

The profile keeps its original thickness even when compensation is required.

Maxiclean

This shower enclosure features the standard Maxiclean treatment, which repels water, avoids limescale and the buildup of dirt, making cleaning easier and keeping the enclosure spotless for longer.

Reversible

Doors may be equally installed for left and right opening.

Profiles in two finishes

Two colours to choose from: polished silver or matt black to obtain the perfect match with the bathroom space.


Without lower profile

In addition to providing enhanced aesthetics, facilitates access to the shower space, making the enclosure more transparent.

Minimalist handle

Brisa includes a practical handle in a fine and 650 mm long and ergonomic design.





Models

Sliding doors

Hidden bearings

Protected by a discreet cover, the bearings remain hidden, offering a more minimalist design.

Soft-close opening and closing

Doors with soft-close opening and closing to avoid unnecessary blows.

Door release system

It features a mechanism that releases the doors from the lower fastening to facilitate the cleaning between glasses.



L2-E + LF-C models joined by a glass sheet

The L2-E and LF-C models are joined without using any profiles by putting both glass sheets together, obtaining enhanced aesthetics and transparency.

Hinged doors

Without overhead support

In the PEF front models of up to 1200mm, a mounting bracket placed on the glass itself provides more robustness and safety, improving the final look.

Vertical movement

When opening and closing, the door slides vertically to avoid brushing against the shower tray, allowing for a 90° opening.

PLF and LF models joined by the glass sheet

The PLF and LF models are joined without using any profiles by putting both glass sheets together, obtaining enhanced aesthetics and transparency.

Easy-cleaning hinges



The hinges in the enclosures are leveled with the inner side of the glass, allowing for easy cleaning and improving the enclosure's design.



Brisa L2-E


Front shower enclosure with 1 sliding door + 1 fixed panel

Reference L2-E	A	Installation dimensions (A) Min-Max	B
AM3431201.M	1200	1160 - 1210	485
AM3431251.M	1250	1211 - 1259	435
AM3431301.M	1300	1260 - 1310	485
AM3431351.M	1350	1311 - 1359	535
AM3431401.M	1400	1360 - 1410	585
AM3431451.M	1450	1411 - 1459	535
AM3431501.M	1500	1460 - 1510	585
AM3431551.M	1550	1511 - 1559	635
AM3431601.M	1600	1560 - 1610	685
AM3431651.M	1650	1611 - 1659	635
AM3431701.M	1700	1660 - 1710	685
AM3431751.M	1750	1711 - 1759	735
AM3431801.M	1800	1760 - 1810	785
AM3431851.M	1850	1811 - 1859	735
AM3431901.M	1900	1860 - 1910	785
AM3431951.M	1950	1911 - 1959	835
AM3432001.M	2000	1960 - 2010	885

**Brisa PEF**

Front shower enclosure with 1 swing door + 1 fixed panel

Reference PEF	A	Installation dimensions (A) Min-Max	Minimum opening
AM3720701.M	700	675 - 700	485
AM3720801.M	800	775 - 800	485
AM3720901.M	900	875 - 900	485
AM3721001.M	1000	975 - 1000	585
AM3721101.M	1100	1075 - 1100	585
AM3721201.M	1200	1175 - 1200	585
AM3721301.M	1300	1275 - 1300	585
AM3721401.M	1400	1375 - 1400	585





Brisa L2-E + LF-C

Front shower enclosure with 1 sliding door
+ 1 fixed panel + 1 side panel

Reference L2-E	A	Installation dimensions (A) Min-Max	B
AM3431201.M	1200	1170 - 1220	485
AM3431251.M	1250	1221 - 1269	435
AM3431301.M	1300	1270 - 1320	485
AM3431351.M	1350	1321 - 1369	535
AM3431401.M	1400	1370 - 1420	585
AM3431451.M	1450	1421 - 1469	535
AM3431501.M	1500	1470 - 1520	585
AM3431551.M	1550	1521 - 1569	635
AM3431601.M	1600	1570 - 1620	685
AM3431651.M	1650	1621 - 1669	635
AM3431701.M	1700	1670 - 1720	685
AM3431751.M	1750	1721 - 1769	735
AM3431801.M	1800	1770 - 1820	785
AM3431851.M	1850	1821 - 1869	735
AM3431901.M	1900	1870 - 1920	785
AM3431951.M	1950	1921 - 1969	835
AM3432001.M	2000	1970 - 2020	885


Reference LF-C	C	Installation dimensions (C) Min-Max
AM3730701.M	700	680 - 700
AM3730801.M	800	780 - 800
AM3730901.M	900	880 - 900

**Brisa PLF + LF**

Front shower enclosure with 1 swing door
+ 1 fixed panel + 1 side panel

Reference PLF	A	Installation dimensions (A) Min-Max	Minimum opening
AM3440701.M	700	665 - 680	485
AM3440801.M	800	765 - 780	485
AM3440901.M	900	865 - 880	485
AM3441001.M	1000	965 - 980	585
AM3441101.M	1100	1065 - 1080	585
AM3441201.M	1200	1165 - 1180	585
AM3441301.M	1300	1265 - 1280	585
AM3441401.M	1400	1365 - 1380	585

Reference LF	C	Installation dimensions (C) Min-Max
AM3740701.M	700	675 - 690
AM3740801.M	800	775 - 790
AM3740901.M	900	875 - 890



The Roca logo consists of the word "Roca" in a bold, white, sans-serif font. Below the letters "o" and "c" is a white horizontal line that curves upwards at both ends, resembling a stylized wave or a bridge.

Roca Sanitario, S.A.

Avda. Diagonal, 513
08029 Barcelona - Spain
+34 933 661 200
roca.com